

Standard felt (depth filtration) or woven Mesh type (surface filtration)

STANDARD (depth filtration):

The felt is made of synthetic fibers of polyester, polypropylene or aramid.

- Filtration from 1 to 200 microns
- Ideal for chemicals
- Sewn or heat sealed construction
- Handle included to ease bag replacement
- Wide range of filter media
- Ideal for high flow rates
- Minimum pressure dropt (chart available on request)
- Choice of metal or plastic ring

STANDARDS (surface filtration):

Woven monofilament and multifilament (nylon, polyester and polypropylene)

- Filtration from 5 to 1000 microns
- Media designed for high flow and low pressure drops (delta P)
- Washable and reusable (NMO and PMO)
- Media release of fibers without fibers will not loose
- Sewn construction
- Handle included to ease bag replacement
- Choice of metal or plastic ring

SIZES:

Overall length (OAL) of the bag (inches)	Diameter (inches)	Length (inches)	Surface (Sq/Ft)	Maximum flow (Gpm)
1	7.25	16.5	2.0	80
2	7.25	32	4.5	180
3	4.31	8	0.5	20
4	4.31	14	1.0	40
7	5.63	15	1.5	60
8	5.63	21	2.0	80
9	5.63	32	3.0	120

Custom sizes also available.



ventes-sales@filtrindustries.com

FILTRINDUSTRIES.COM



37, rue John-A.-Scott
Lévis (Québec)
G6Z 8K8

T 418 832-1415

F 418 832-8474