

37 rue John-A.-Scott Lévis, Québec, G6Z 8K8

www.filtrindustries.com 1-888-FILTRES




FILTRATION AND LUBRICATION PRODUCTS FOR COMPRESSED AIR SYSTEMS

- Standard 5-micron rating
- Lower micron ratings available
- SCFM range 15 thru 2000
- Dewpoints 10° to 35°F at atmosphere
- Easy to install and maintain
- Modular design can expand to 4 stages if needed
 - Standard Differential Pressure Gauge
 - Standard Weep Drain

APPLICATIONS:

- Air Guns
- Injection Molding
- Hospital Equipment
- Staple Guns
- Printing Presses
- Air Operated Chucks
- Auto Paint & Body Shop
- Sandblasting
- Air Doors
- Air Brushes

- Rivet Guns
- Bakery Equipment
- Textile Needles
- Package Coding
- Transit Systems
- Dental Equipment
- Nailers
- Brewery Bottling
- Construction
- Electronics



How it Works -

- ① Compressed air containing tiny particles of dirt, dust, oil, rust and moisture, enters the first stage of the LaMan® Extractor/Dryer Filter.
- **2** A coalescing effect occurs as air passes through a cartridge mesh filter which captures larger particles and causes moisture to form larger droplets.
- **3** Air velocity lessens as it enters the extraction chamber allowing particles to collect and moisture to condense on the honeycomb.
- 4 Particle-laden liquid flows along the bottom and out the drain.
- **5** Air passes through the second stage wire supported fiber filter cartridge which captures remaining particles down to 5 microns.
- **6** Remaining moisture and contaminants are dried and filtered in the second stage filter.
- © Exhaust air is clean and dry no dirt, rust, oil, or water drops to disrupt air equipment operation.

SPECIFICATIONS											
Model	520A	520B	105	106	107	110	111	120	140	180	195A
NPT	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"	3/4"	1"	1 ½"	2"	4" Flange
SCFM	15	15	50	50	50	80	80	150	250	500	2000
MAX. PSI	250	250	250	250	250	250	250	250	250	150	150
SIZE	7½ x	8¼ x	8¼ x	8¼ x	8¼ x	11¾ x	11¾ x	15 x 9½	20 x 12½	27 x 18	42½ x
	3 x 11/4	3 x 1¾	4 x 2½	4 x 2½	4 x 2½	6 x 3¼	6 x 31/4	x 5½	x 7¼	x 9¾	32 x 17
APPR. WT.	2#	2#	3#	3#	3#	6#	6#	15#	36#	70#	375#
Service Kit #	015SK	015SK	050SK	050SK	050SK	080SK	080SK	150SK	250SK	500SK	493-494



MODEL 120F with Differential Pressure Gauge and optional Float Drain

